

PRODUCT DESCRIPTION

When it comes to lighting a large area, this product is the ideal solution for high impact lighting of mine-haul road intersections, road works, construction sites, events and general industrial and maintenance programs.

SPECIFICATIONS/FEATURES

- » Input Voltage: 100-277V / 50-60Hz
- » Type of installation: Portable
- » Resistance dimming
- » Colour handle: Black
- » Power supply cable: SJTW 18AWG*3C / 5M(16.40ft)
- » Lamp cover: opal
- » >125LM/W in a Luminaire
- » Type of protection: Ip54
- » Protection class: II
- » Glow wire test: 850°C - 30 seconds
- » Impact protection: IK08 (5 Joule)
- » 5 year limited warranty



*for approved
fixture categories



A++




125Lm/W



SJTW 18AWG*3C / 5M(16.40ft)



-40°F to 122°F (-40°C to +50°C)



Switch function available



Dimensions Wattage	H	D	Ø
80W	360mm / 14.17"	265mm / 10.43"	250mm / 9.84"
120W	560mm / 22.05"	265mm / 10.43"	250mm / 9.84"
220W	820mm / 32.28"	265mm / 10.43"	250mm / 9.84"



TECHNICAL SPECIFICATIONS

Model No.	Wattage (W)+/- 10%	AC Input	Lumens +/- 5%	CCT.	PF	Dimensions H*D	Weight	Per Carton	Certificate
YL-WL10-80W-M-XXK	80	100~277V ac 50/60Hz	10,000	2700-6500K	≥0.9	360*265(mm) 14.17"x10.43"	NW 4.85Kg 11lbs	1pc GW 5.75Kg/13lbs	ETL
YL-WL10-120W-M-XXK	120	100~277V ac 50/60Hz	15,000	2700-6500K	≥0.9	560*265(mm) 22.05"x10.43"	NW 7.05Kg 16lbs	1pc GW 8.05Kg/18lbs	ETL
YL-WL10-220W-M-XXK	220	100~277V ac 50/60Hz	27,500	2700-6500K	≥0.9	820*265(mm) 32.28"x10.43"	NW 8.60Kg 19lbs	1pc GW 9.95Kg/22lbs	ETL

* Kelvin Temperatures may vary +/- 250K.

* Line length of Please inquire. Extending the power cord may increase the size of the package.